



## Declaration of Performance

Kingspan Kooltherm® K110 Soffit Board

1000.CPR.2013.K110.007

Unique identification code of the product-type:

Intended use/es:

Manufacturer: System/s of AVCP:

Harmonised technical specification

Notified body/ies:

Kingspan Kooltherm® K110 Soffit Board

Thermal insulation for buildings

Kingspan Insulation Ltd, Herefordshire HR6 9LA, UK System 1 (Reaction to Fire), System 3 (Other Properties)

BS EN 13166:2012+A2:2016

Efectis: 1812. KIWA: 0063. FIW München: 0751

| Notified body/ies:   | Efectis: 1812, KIWA: 0063, FIW München: 0751                                    |   |  |
|--|---|---|--|
| Essential characteristics  |   | Performance   |  |
| Thermal resistance   | Thermal resistance R <sub>D</sub> ((m².K)/W)                                    | dN 65mm 3.40   dN 70mm 3.65   dN 75mm 3.90   dN 80mm 4.20   dN 85mm 4.45   dN 90mm 4.70   dN 100mm 5.25   dN 110mm 5.75   dN 120mm 6.30 |  |
|  | Thermal conductivity $\lambda_D$ (W/(m.K))                                      | λ <sub>D</sub> 0.019  |  |
|  | Thickness tolerance   | П   |  |
| Reaction to fire   | Reaction to fire  | C-s2,d0   |  |
| Durability of reaction to fire against heat, weathering, ageing / degradation        | Durability Characteristics  | NPD   |  |
| Durability of thermal resistance<br>against heat, weathering,<br>ageing/ degradation | Durability Characteristics  | NPD   |  |
|  | Dimensional stability under specified temperature and humidity condition        | DS(70,90)   |  |
|  |   | D\$(-20,-)  |  |
|  | Determination of the aged values of thermal resistance and thermal conductivity | $R_D$ and $\lambda_D$   |  |
| Compressive strength   | Compressive stress or compressive strength                                      | CS(Y)100  |  |
| Tensile / Flexural strength  | Tensile strength perpendicular to faces   | NPD   |  |
| Durability of compressive strength against ageing / degradation                      | Compressive creep   | NPD   |  |
| Water permeability   | Short term water absorption   | NPD   |  |
|  | Long term water absorption  | NPD   |  |
|  | Closed cell content   | CV  |  |





## Declaration of Performance

| Water vapour permeability                                 | Water vapour transmission       | NPD |
|---|---------------------------------|-----|
|   | Closed cell content             | CV  |
| Release of dangerous substances to the indoor environment | Release of dangerous substances | NPD |
| NPD: No Performance Determined                            |                                 |     |

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

For System 1 AVCP Notified certification body No 1812 Performed, carried out the determination of the product type, the inspection of the manufacturing plant and factory production control and continuous surveillance, assessment and evaluation of the factory production control, and issued the certificate of constancy of performance for reaction to fire, cert No 1812 – CPR - 1992

Notified testing lab 0063 and 0751 Performed the test reports for the other relevant declared characteristics (AVCP 3 properties).

Signed for and on behalf of the manufacturer by:

.....

Siobhan O'Dwyer Managing Director

Pembridge, England, UK Date Signed: 26/09/2024 Version Number: 007



For the most up-to-date version of the Declaration of Performance please scan or <u>click here</u>.

To access pre-existing product information or information relating to previously sold/discontinued products please email literature@kingspaninsulation.co.uk.