



# Declaration of Performance

Kingspan Kooltherm® K112 Framing Board

1000.CPR.2013.K112.007

Unique identification code of the product-type:  
Intended use/es:  
Manufacturer:  
System/s of AVCP:  
Harmonised technical specification  
Notified body/ies:

**Kingspan Kooltherm® K112 Framing Board**  
**Thermal insulation for buildings**  
**Kingspan Insulation Ltd, Herefordshire HR6 9LA, UK**  
**System 4 (Reaction to fire), System 3 (Other Properties)**  
**BS EN 13166:2012+A2:2016**  
**KIWA:1640, FIW:0751**

Essential characteristics		Performance																														
Thermal resistance	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	<table border="1"> <tr><td>d<sub>N</sub> 25mm</td><td>1.30</td></tr> <tr><td>d<sub>N</sub> 30mm</td><td>1.55</td></tr> <tr><td>d<sub>N</sub> 40mm</td><td>2.10</td></tr> <tr><td>d<sub>N</sub> 50mm</td><td>2.60</td></tr> <tr><td>d<sub>N</sub> 60mm</td><td>3.15</td></tr> <tr><td>d<sub>N</sub> 70mm</td><td>3.65</td></tr> <tr><td>d<sub>N</sub> 75mm</td><td>3.90</td></tr> <tr><td>d<sub>N</sub> 80mm</td><td>4.20</td></tr> <tr><td>d<sub>N</sub> 90mm</td><td>4.70</td></tr> <tr><td>d<sub>N</sub> 100mm</td><td>5.25</td></tr> <tr><td>d<sub>N</sub> 110mm</td><td>5.75</td></tr> <tr><td>d<sub>N</sub> 120mm</td><td>6.30</td></tr> <tr><td>d<sub>N</sub> 130mm</td><td>6.80</td></tr> <tr><td>d<sub>N</sub> 140mm</td><td>7.35</td></tr> <tr><td>d<sub>N</sub> 150mm</td><td>7.85</td></tr> </table>	d <sub>N</sub> 25mm	1.30	d <sub>N</sub> 30mm	1.55	d <sub>N</sub> 40mm	2.10	d <sub>N</sub> 50mm	2.60	d <sub>N</sub> 60mm	3.15	d <sub>N</sub> 70mm	3.65	d <sub>N</sub> 75mm	3.90	d <sub>N</sub> 80mm	4.20	d <sub>N</sub> 90mm	4.70	d <sub>N</sub> 100mm	5.25	d <sub>N</sub> 110mm	5.75	d <sub>N</sub> 120mm	6.30	d <sub>N</sub> 130mm	6.80	d <sub>N</sub> 140mm	7.35	d <sub>N</sub> 150mm	7.85
	d <sub>N</sub> 25mm	1.30																														
	d <sub>N</sub> 30mm	1.55																														
d <sub>N</sub> 40mm	2.10																															
d <sub>N</sub> 50mm	2.60																															
d <sub>N</sub> 60mm	3.15																															
d <sub>N</sub> 70mm	3.65																															
d <sub>N</sub> 75mm	3.90																															
d <sub>N</sub> 80mm	4.20																															
d <sub>N</sub> 90mm	4.70																															
d <sub>N</sub> 100mm	5.25																															
d <sub>N</sub> 110mm	5.75																															
d <sub>N</sub> 120mm	6.30																															
d <sub>N</sub> 130mm	6.80																															
d <sub>N</sub> 140mm	7.35																															
d <sub>N</sub> 150mm	7.85																															
Thermal conductivity $\lambda_D$ (W/(m.K))	$\lambda_D$ 0.019																															
Thickness tolerance	T1																															
Reaction to fire	Reaction to fire	F																														
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD																														
Durability of thermal resistance against heat, weathering, ageing/ degradation	Durability Characteristics	NPD																														
	Dimensional stability under specified temperature and humidity condition	DS(70,90)																														
		DS(-20,-)																														
Determination of the aged values of thermal resistance and thermal conductivity	$R_D$ and $\lambda_D$																															
Compressive strength	Compressive stress or compressive strength	CS(Y)100																														
Tensile / Flexural strength	Tensile strength perpendicular to faces	NPD																														
Durability of compressive strength against ageing / degradation	Compressive creep	NPD																														
Water permeability	Short term water absorption	NPD																														



# Declaration of Performance

	Long term water absorption	NPD
	Closed cell content	CV
Water vapour permeability	Water vapour transmission	NPD
	Closed cell content	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
Continuous Glowing Combustion	Glowing combustion	NPD
NPD: No Performance Determined		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

**Signed for and on behalf of the manufacturer by:**

.....  
**Siobhan O'Dwyer**  
**Managing Director**  
**Pembridge, England, UK**  
**Date signed: 26/09/2024**  
**Version Number: 007**



For the most up-to-date version of the Declaration of Performance please scan or [click here](#).

To access pre-existing product information or information relating to previously sold/discontinued products please email [literature@kingspaninsulation.co.uk](mailto:literature@kingspaninsulation.co.uk).