

UK Declaration of Performance

Kingspan Thermarroof® TR24 PB (Pre-Bonded)

1000.UKDoP.TR24PB.003

Unique identification code of the product-type: **Kingspan Thermarroof® TR24 PB (Pre-Bonded)**
 Intended use/es: **Thermal insulation for buildings**
 Manufacturer: **Kingspan Insulation Ltd, Herefordshire HR6 9LA, UK**
 System/s of AVCP: **System 4 (Reaction to fire), System 3 (Other Properties)**
 Designated technical specification: **BS EN 13165:2012+A2:2016**
 UK Assessment/Notified body: **University of Salford: 1145, BBA: 0836**

Essential characteristics		Performance	
Thermal resistance	Thermal resistance R_D ((m ² .K)/W)		6.40
			6.85
			7.25
		d_N 160mm (80mm + 80mm)	7.65
		d_N 170mm (120mm + 50mm)	8.10
		d_N 180mm (130mm + 50mm)	8.60
		d_N 190mm (140mm + 50mm)	9.00
		d_N 200mm (150mm + 50mm)	9.45
		d_N 210mm (130mm + 80mm)	9.80
		d_N 220mm (140mm + 80mm)	10.25
		d_N 230mm (150mm + 80mm)	10.80
		d_N 240mm (140mm + 100mm)	11.25
		d_N 250mm (150mm + 100mm)	11.65
		d_N 260mm (140mm + 120mm)	
		d_N 270mm (150mm + 120mm)	
d_N 280mm (150mm + 130mm)			
Thermal conductivity λ_D (W/(m.K))	$d_N < 80$ mm	0.027	
	d_N 80-119mm	0.025	
	$d_N \geq 120$ mm	0.024	
The Thermal Conductivity listed above is for the single board components used to make up the pre-bonded product only. For the full Thermal resistance, see above table.			
Thickness tolerance	T2		
Reaction to fire	Reaction to fire	F	

UK Declaration of Performance

Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of the reaction to fire of the product as placed on the market	NPD						
	Durability of thermal resistance and thermal conductivity against ageing/ degradation	NPD						
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal resistance RD ((m ² .K)/W)	Thermal resistance as table above						
	Thermal conductivity λD (W/(m.K))	<table border="0"> <tr> <td>dN < 80mm</td> <td>0.027</td> </tr> <tr> <td>dN 80-119mm</td> <td>0.025</td> </tr> <tr> <td>dN ≥ 120mm</td> <td>0.024</td> </tr> </table> <p>The Thermal Conductivity listed above is for the single board components used to make up the pre-bonded product only. For the full Thermal resistance, see above table.</p>	dN < 80mm	0.027	dN 80-119mm	0.025	dN ≥ 120mm	0.024
	dN < 80mm	0.027						
	dN 80-119mm	0.025						
	dN ≥ 120mm	0.024						
Durability characteristics	NPD							
Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1							
Deformation under specified compressive load and temperature conditions	NPD							
Determination of the aged values of thermal resistance and thermal conductivity	λD 0,024, 0.025, 0,027 W/m-K							
Compressive strength	Compressive stress or compressive strength	CS(10\Y)150						
Tensile / Flexural strength	Tensile strength perpendicular to faces	NPD						
Durability of compressive strength against ageing / degradation	Compressive creep	NPD						
Water permeability	Short term water absorption	NPD						
	Long term water absorption	NPD						
	Flatness after one sided wetting	NPD						
Water vapour permeability	Water vapour transmission	NPD						
Acoustic absorption index	Sound absorption	NPD						
Continuous Glowing Combustion	Glowing Combustion	NPD						
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD						
NPD: No Performance Determined								

EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2020.)

**UK
CA**



UK Declaration of Performance

Signed for and on behalf of the manufacturer by:

.....
Siobhan O'Dwyer
Managing Director
Pembridge, England, UK
Date signed: 19/09/2024
Issue Number: 003



For the most up-to-date version of the Declaration of Performance please scan or [click here](#).

To access pre-existing product information or information relating to previously sold/discontinued products please email literature@kingspaninsulation.co.uk