

K-Roc™ HF Series Load / Span Tables

26/26 facer gauges; 16 ga (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 5"	11' - 8"	9' - 10"	8' - 7"	7' - 7"	6' - 10"
	Multiple Span	14' - 9"	11' - 10"	9' - 11"	8' - 7"	7' - 6"	6' - 9"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 4"	13' - 2"	10' - 8"	8' - 11"	7' - 7"	6' - 8"
	Multiple Span	16' - 5"	13' - 0"	10' - 8"	9' - 0"	7' - 10"	6' - 10"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 6"	12' - 9"	10' - 4"	8' - 7"	7' - 4"	6' - 5"
	Multiple Span	16' - 3"	12' - 10"	10' - 6"	8' - 10"	7' - 7"	6' - 8"

Panel series:	K-Roc HF (Shadowline)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	26 ga AZ50 steel
Interior face:	26 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	16 ga (50 ksi) supports
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (829 lbs/fastener)

Note: Consult Kingspan for project-specific applications.

24/26 facer gauges; 16 ga (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 6"	11' - 9"	9' - 11"	8' - 7"	7' - 7"	6' - 10"
	Multiple Span	14' - 9"	11' - 11"	9' - 11"	8' - 7"	7' - 7"	6' - 9"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 5"	13' - 1"	10' - 7"	8' - 10"	7' - 7"	6' - 7"
	Multiple Span	16' - 5"	12' - 11"	10' - 8"	9' - 0"	7' - 9"	6' - 10"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 5"	12' - 8"	10' - 3"	8' - 7"	7' - 4"	6' - 5"
	Multiple Span	16' - 3"	12' - 9"	10' - 5"	8' - 10"	7' - 7"	6' - 8"

Panel series:	K-Roc HF (Azteco™, Micro-Rib, Shadowline)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	24 ga AZ50 steel
Interior face:	26 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	16 ga (50 ksi) supports
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (829 lbs/fastener)

Note: Consult Kingspan for project-specific applications.



K-Roc™ HF Series Load / Span Tables

24/24 facer gauges; 16 ga (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 6"	11' - 9"	9' - 11"	8' - 8"	7' - 8"	6' - 10"
	Multiple Span	14' - 10"	11' - 11"	10' - 0"	8' - 7"	7' - 7"	6' - 9"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 5"	13' - 0"	10' - 6"	8' - 9"	7' - 6"	6' - 6"
	Multiple Span	16' - 4"	12' - 11"	10' - 7"	8' - 11"	7' - 9"	6' - 9"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 3"	12' - 7"	10' - 2"	8' - 6"	7' - 3"	6' - 4"
	Multiple Span	16' - 2"	12' - 9"	10' - 5"	8' - 9"	7' - 6"	6' - 7"

Panel series:	K-Roc HF (Shadowline, Azteco, Mini Micro-Rib)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	24 ga AZ50 steel
Interior face:	24 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	16ga (50 ksi) supports
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (829 lbs/fastener)

Note: Consult Kingspan for project-specific applications.

22/22 facer gauges; 16 ga (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 8"	11' - 11"	10' - 1"	8' - 9"	7' - 8"	6' - 8"
	Multiple Span	14' - 10"	12' - 0"	10' - 1"	8' - 8"	7' - 8"	6' - 10"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 6"	12' - 9"	10' - 3"	8' - 7"	7' - 4"	6' - 5"
	Multiple Span	16' - 3"	12' - 10"	10' - 6"	8' - 10"	7' - 7"	6' - 8"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 0"	12' - 4"	9' - 11"	8' - 4"	7' - 2"	6' - 3"
	Multiple Span	16' - 0"	12' - 7"	10' - 3"	8' - 8"	7' - 5"	6' - 6"

Panel series:	K-Roc HF (Shadowline, Azteco, Mini Micro-Rib)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	22 ga AZ50 steel
Interior face:	22 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	16ga (50 ksi) supports
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (829 lbs/fastener)

Note: Consult Kingspan for project-specific applications.



K-Roc™ HF Series Load / Span Tables

26/26 facer gauges; 12 ga (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 5"	11' - 8"	9' - 10"	8' - 7"	7' - 7"	6' - 10"
	Multiple Span	14' - 9"	11' - 10"	9' - 11"	8' - 7"	7' - 6"	6' - 9"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 11"	13' - 2"	10' - 8"	8' - 11"	7' - 7"	6' - 8"
	Multiple Span	16' - 5"	13' - 0"	10' - 8"	9' - 0"	7' - 10"	6' - 10"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 6"	12' - 9"	10' - 4"	8' - 7"	7' - 4"	6' - 5"
	Multiple Span	16' - 3"	12' - 10"	10' - 6"	8' - 10"	7' - 7"	6' - 8"

Panel series:	K-Roc HF (Shadowline)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	26 ga AZ50 steel
Interior face:	26 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	12 ga (50 ksi) supports
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (1450 lbs/fastener)

Note: Consult Kingspan for project-specific applications.

24/26 facer gauges; 12 ga (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 6"	11' - 9"	9' - 11"	8' - 7"	7' - 7"	6' - 10"
	Multiple Span	14' - 6"	11' - 11"	9' - 11"	8' - 7"	7' - 7"	6' - 9"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 9"	13' - 1"	10' - 7"	8' - 10"	7' - 7"	6' - 7"
	Multiple Span	16' - 5"	12' - 11"	10' - 8"	9' - 0"	7' - 9"	6' - 10"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 5"	12' - 8"	10' - 3"	8' - 7"	7' - 4"	6' - 5"
	Multiple Span	16' - 3"	12' - 9"	10' - 5"	8' - 10"	7' - 7"	6' - 8"

Panel series:	K-Roc HF (Azteco, Micro-Rib, Shadowline)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	24 ga AZ50 steel
Interior face:	26 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	12 ga (50 ksi) supports
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (1450 lbs/fastener)

Note: Consult Kingspan for project-specific applications.



K-Roc™ HF Series Load / Span Tables

24/24 facer gauges; 12 ga (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 6"	11' - 9"	9' - 11"	8' - 8"	7' - 8"	6' - 10"
	Multiple Span	14' - 10"	11' - 11"	10' - 0"	8' - 7"	7' - 7"	6' - 9"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 8"	13' - 0"	10' - 6"	8' - 9"	7' - 6"	6' - 6"
	Multiple Span	16' - 4"	12' - 11"	10' - 7"	8' - 11"	7' - 9"	6' - 9"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 3"	12' - 7"	10' - 2"	8' - 6"	7' - 3"	6' - 4"
	Multiple Span	16' - 2"	12' - 9"	10' - 5"	8' - 9"	7' - 6"	6' - 7"

Panel series:	K-Roc HF (Azteco, Micro-Rib, Shadowline)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	24 ga AZ50 steel
Interior face:	24 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	12 ga (50 ksi) supports
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (1450 lbs/fastener)

Note: Consult Kingspan for project-specific applications.

22/22 facer gauges; 12 ga (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 8"	11' - 11"	10' - 1"	8' - 9"	7' - 8"	6' - 8"
	Multiple Span	14' - 10"	12' - 0"	10' -1"	8' -8"	7' - 8"	6' - 10"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 6"	12' - 9"	10' - 3"	8' - 7"	7' - 4"	6' - 5"
	Multiple Span	16' - 3"	12' - 10"	10' - 6"	8' - 10"	7' - 7"	6' - 8"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 0"	12' - 4"	9' - 11"	8' - 4"	7' - 2"	6' - 3"
	Multiple Span	16' - 0"	12' - 7"	10' - 3"	8' - 8"	7' - 5"	6' - 6"

Panel series:	K-Roc HF (Azteco, Micro-Rib, Shadowline)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	22 ga AZ50 steel
Interior face:	22 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	12 ga (50 ksi) supports
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (1450 lbs/fastener)

Note: Consult Kingspan for project-specific applications.



K-Roc™ HF Series Load / Span Tables

26/26 facer gauges; 1/4" (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 5"	11' - 8"	9' - 10"	8' - 7"	7' - 7"	6' - 10"
	Multiple Span	14' - 9"	11' -10"	9' - 11"	8' - 7"	7' - 6"	6' - 9"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' -11"	13' - 2"	10' - 8"	8' - 11"	7' - 7"	6' - 8"
	Multiple Span	16' - 5"	13' - 0"	10' - 8"	9' - 0"	7' - 10"	6' - 10"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 6"	12' - 9"	10' - 4"	8' - 7"	7' - 4"	6' - 5"
	Multiple Span	16' - 3"	12' - 10"	10' - 6"	8' -10"	7' - 7"	6' - 8"

Panel series:	K-Roc HF (Shadowline)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	26 ga AZ50 steel
Interior face:	26 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	1/4"
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (3453 lbs/fastener)

Note: Consult Kingspan for project-specific applications.

24/26 facer gauges; 1/4" (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 6"	11' - 9"	9' - 11"	8' - 7"	7' - 7"	6' - 10"
	Multiple Span	14' - 9"	11' - 11"	9' - 11"	8' -7"	7' - 7"	6' - 9"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 10"	13' - 1"	10' - 7"	8' - 10"	7' - 7"	6' - 7"
	Multiple Span	16' - 5"	12' - 11"	10' - 8"	9' - 0"	7' - 9"	6' - 10"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 5"	12' - 8"	10' - 3"	8' - 7"	7' - 4"	6' - 5"
	Multiple Span	16' - 3"	12' - 9"	10' - 5"	8' - 10"	7' - 7"	6' - 8"

Panel series:	K-Roc HF (Azteco, Micro-Rib, Shadowline)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	24 ga AZ50 steel
Interior face:	26 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	1/4"
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (3453 lbs/fastener)

Note: Consult Kingspan for project-specific applications.



K-Roc™ HF Series Load / Span Tables

24/24 facer gauges; 1/4" (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 6"	11' - 9"	9' - 11"	8' - 8"	7' - 8"	6' - 10"
	Multiple Span	14' - 10"	11' -11"	10' - 0"	8' - 7"	7' - 7"	6' - 9"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 8"	13' - 0"	10' - 6"	8' - 9"	7' - 6"	6' - 6"
	Multiple Span	16' - 4"	12' - 11"	10' - 7"	8' - 11"	7' - 9"	6' - 3"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 3"	12' - 7"	10' - 2"	8' - 6"	7' - 3"	6' - 4"
	Multiple Span	16' - 2"	12' - 9"	10' - 5"	8' -9"	7' - 6"	6' - 7"

Panel series:	K-Roc HF (Azteco, Micro-Rib, Shadowline)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	24 ga AZ50 steel
Interior face:	24 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	1/4"
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (3453 lbs/fastener)

Note: Consult Kingspan for project-specific applications.

22/22 facer gauges; 1/4" (50 ksi) supports							
Mid-span through-fastening							
Panel Thickness	Span Condition	Negative Wall Pressure in PSF					
		20 PSF	25 PSF	30 PSF	35 PSF	40 PSF	45 PSF
4"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	14' - 8"	11' - 11"	10' - 1"	8' - 9"	7' - 8"	6' - 8"
	Multiple Span	14' - 10"	12' - 0"	10' - 1"	8' - 6"	8' - 8"	7' - 8"
6"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 6"	12' - 9"	10' - 3"	8' - 7"	7' - 4"	6' - 5"
	Multiple Span	16' - 3"	12' - 10"	10' - 6"	8' - 10"	7' - 7"	6' - 8"
8"	Single Span	13' - 5"	10' - 8"	8' - 11"	7' - 8"	6' - 8"	5' - 11"
	Double Span	16' - 6"	12' - 9"	10' - 3"	8' - 7"	7' - 4"	6' - 5"
	Multiple Span	16' - 3"	12' - 10"	10' - 6"	8' - 10"	7' - 7"	6' - 8"

Panel series:	K-Roc HF (Azteco, Micro-Rib, Shadowline)
Design parameter:	Uniform load
Fastening method:	Concealed panel clip with (2) x 1/4"-14 self-drilling fasteners with (3) 1/4"-14 exposed fasteners with 1-1/8" dia. bonded washers at every support
Exterior face:	22 ga AZ50 steel
Interior face:	22 ga AZ50 steel
Deflection limit:	L/180
Structural support gauge:	1/4"
Panel width:	42"
Thermal differential:	Not considered
Fastener pull-out values:	Based on published data for 1/4"-14 Triangle Blazer fasteners (3453 lbs/fastener)

Note: Consult Kingspan for project-specific applications.



Contact Details

USA

DeLand, FL: 877-638-3266
Modesto, CA: 800-377-5110

info.NA@kingspanpanels.com
www.kingspanpanels.us



[Latest version here](#)

Canada

Caledon, ON: 866-442-3594
Langley, BC: 877-937-6562

info.NA@kingspanpanels.com
www.kingspanpanels.ca



[Latest version here](#)

For the most up to date version of this document,
please scan the QR codes above or click the link.

Care has been taken to ensure that the contents of this publication are accurate, but Kingspan Limited and its subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use or application of products or methods of working are for information only and Kingspan Limited and its subsidiaries accept no liability in respect thereof. Kingspan Limited and its subsidiaries do not assume responsibility for the completeness, correctness or quality of third-party information.
© Kingspan and the Lion Device are Registered Trademarks of the Kingspan Group plc in the US, Canada and other countries. K-Roc is a Trademark of Kingspan Group plc. All rights reserved. © Kingspan Insulated Panels Inc.

