

KingRib® 3 Wall Allowable Load / Span Tables

Facer Gauges: 26 ga exterior / 26 ga interior

| Steel Support: 3/16" |                |                        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
|----------------------|----------------|------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Panel Thickness      | Span Condition | Negative Wind Pressure |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
|                      |                | 20 PSF                 | 25 PSF | 30 PSF | 35 PSF | 40 PSF | 45 PSF | 50 PSF | 55 PSF | 60 PSF | 65 PSF | 70 PSF | 75 PSF | 80 PSF | 85 PSF | 90 PSF |
| 2.5"                 | Single         | 10'-2"                 | 9'-1"  | 8'-4"  | 7'-8"  | 7'-2"  | 6'-9"  | 6'-5"  | 6'-1"  | 5'-10" | 5'-8"  | 5'-5"  | 5'-2"  | 4'-11" | 4'-8"  | 4'-6"  |
|                      | Double         | 9'-3"                  | 7'-11" | 7'-0"  | 6'-4"  | 5'-9"  | 5'-4"  | 5'-0"  | 4'-8"  | 4'-5"  | 4'-2"  | 3'-11" | 3'-9"  | 3'-7"  | 3'-5"  | 3'-4"  |
|                      | Multiple       | 10'-2"                 | 8'-9"  | 7'-8"  | 6'-11" | 6'-3"  | 5'-9"  | 5'-4"  | 5'-0"  | 4'-9"  | 4'-6"  | 4'-3"  | 4'-1"  | 3'11"  | 3'-9"  | 3'-7"  |
| 4"                   | Single         | 12'-8"                 | 11'-4" | 10'-4" | 9'-6"  | 8'-11" | 8'-5"  | 7'-11" | 7'-7"  | 7'-3"  | 6'-11" | 6'-8"  | 6'-6"  | 6'-3"  | 6'-1"  | 5'-11" |
|                      | Double         | 10'-11"                | 9'-3"  | 8'-2"  | 7'-3"  | 6'-7"  | 6'-1"  | 5'-7"  | 5'-3"  | 4'-11" | 4'-7"  | 4'-4"  | 4'-2"  | 4'-0"  | 3'-9"  | 3'-8"  |
|                      | Multiple       | 11'-10"                | 10'-1" | 8'-9"  | 7'-10" | 7'-1"  | 6'-6"  | 6'-0"  | 5'-7"  | 5'-3"  | 4'-11" | 4'-8"  | 4'-5"  | 4'-3"  | 4'-0"  | 3'-11" |

|                                                         |                                                                              |
|---------------------------------------------------------|------------------------------------------------------------------------------|
| Deflection Limit:                                       | L/180                                                                        |
| Fastening Method:                                       | (4) 1/4"-14" Through-Screws with 1 1/8" washer at every support              |
| Wind Pressure:                                          | Nominal, ASD, Service Loads                                                  |
| Thermal Differential:                                   | EXCLUDED                                                                     |
| Minimum Support Steel Properties:                       | 3/16" Grade 36 (Fu = 58 ksi)                                                 |
| DB Fastener pull-out values per supporting steel gauge: | 16 ga = 785 lbs, 14 ga = 1,035 lbs, 12 ga = 1,665 lbs, and 3/16" = 3,115 lbs |

Notes to tables: Spans shown are for negative uniform loads only. Spans may be governed by other factors including temperature differentials, deflection requirements, structural support gage, or unequal spacing of secondary. Consult Kingspan for specific project applications.



KingRib® 3 Wall Allowable Load / Span Tables

Facer Gauges: 26 ga exterior / 26 ga interior

| Steel Support: 12 ga |                |                        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
|----------------------|----------------|------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Panel Thickness      | Span Condition | Negative Wind Pressure |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
|                      |                | 20 PSF                 | 25 PSF | 30 PSF | 35 PSF | 40 PSF | 45 PSF | 50 PSF | 55 PSF | 60 PSF | 65 PSF | 70 PSF | 75 PSF | 80 PSF | 85 PSF | 90 PSF |
| 2.5"                 | Single         | 10'-2"                 | 9'-1"  | 8'-4"  | 7'-8"  | 7'-2"  | 6'-9"  | 6'-5"  | 6'-1"  | 5'-10" | 5'-8"  | 5'-5"  | 5'-2"  | 4'-11" | 4'-8"  | 4'-6"  |
|                      | Double         | 9'-3"                  | 7'-11" | 7'-0"  | 6'-4"  | 5'-9"  | 5'-4"  | 5'-0"  | 4'-8"  | 4'-5"  | 4'-2"  | 3'-11" | 3'-9"  | 3'-7"  | 3'-5"  | 3'-4"  |
|                      | Multiple       | 10'-2"                 | 8'-9"  | 7'-8"  | 6'-11" | 6'-3"  | 5'-9"  | 5'-4"  | 5'-0"  | 4'-9"  | 4'-6"  | 4'-3"  | 4'-1"  | 3'-11" | 3'-9"  | 3'-7"  |
| 4"                   | Single         | 12'-8"                 | 11'-4" | 10'-4" | 9'-6"  | 8'-11" | 8'-5"  | 7'-11" | 7'-7"  | 7'-3"  | 6'-11" | 6'-8"  | 6'-6"  | 6'-3"  | 6'-1"  | 5'-11" |
|                      | Double         | 10'-11"                | 9'-3"  | 8'-2"  | 7'-3"  | 6'-7"  | 6'-1"  | 5'-7"  | 5'-3"  | 4'-11" | 4'-7"  | 4'-4"  | 4'-2"  | 4'-0"  | 3'-9"  | 3'-8"  |
|                      | Multiple       | 11'-10"                | 10'-1" | 8'-9"  | 7'-10" | 7'-1"  | 6'-6"  | 6'-0"  | 5'-7"  | 5'-3"  | 4'-11" | 4'-8"  | 4'-5"  | 4'-3"  | 4'-0"  | 3'-11" |

|                                                         |                                                                              |
|---------------------------------------------------------|------------------------------------------------------------------------------|
| Deflection Limit:                                       | L/180                                                                        |
| Fastening Method:                                       | (4) 1/4"-14" Through-Screws with 1 1/8" washer at every support              |
| Wind Pressure:                                          | Nominal, ASD, Service Loads                                                  |
| Thermal Differential:                                   | EXCLUDED                                                                     |
| Minimum Support Steel Properties:                       | 12 ga Grade 50 (Fu = 65 ksi)                                                 |
| DB Fastener pull-out values per supporting steel gauge: | 16 ga = 785 lbs, 14 ga = 1,035 lbs, 12 ga = 1,665 lbs, and 3/16" = 3,115 lbs |

Notes to tables: Spans shown are for negative uniform loads only. Spans may be governed by other factors including temperature differentials, deflection requirements, structural support gage, or unequal spacing of secondary. Consult Kingspan for specific project applications.



KingRib® 3 Wall Allowable Load / Span Tables

Facer Gauges: 26 ga exterior / 26 ga interior

| Steel Support: 14 ga |                |                        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
|----------------------|----------------|------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Panel Thickness      | Span Condition | Negative Wind Pressure |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
|                      |                | 20 PSF                 | 25 PSF | 30 PSF | 35 PSF | 40 PSF | 45 PSF | 50 PSF | 55 PSF | 60 PSF | 65 PSF | 70 PSF | 75 PSF | 80 PSF | 85 PSF | 90 PSF |
| 2.5"                 | Single         | 10'-2"                 | 9'-1"  | 8'-4"  | 7'-8"  | 7'-2"  | 6'-9"  | 6'-5"  | 6'-1"  | 5'-10" | 5'-8"  | 5'-5"  | 5'-2"  | 4'-11" | 4'-8"  | 4'-6"  |
|                      | Double         | 9'-3"                  | 7'-11" | 7'-0"  | 6'-4"  | 5'-9"  | 5'-4"  | 5'-0"  | 4'-8"  | 4'-5"  | 4'-2"  | 3'-11" | 3'-9"  | 3'-7"  | 3'-5"  | 3'-4"  |
|                      | Multiple       | 10'-2"                 | 8'-9"  | 7'-8"  | 6'-11" | 6'-3"  | 5'-9"  | 5'-4"  | 5'-0"  | 4'-9"  | 4'-6"  | 4'-3"  | 4'-1"  | 3'-11" | 3'-9"  | 3'-7"  |
| 4"                   | Single         | 12'-8"                 | 11'-4" | 10'-4" | 9'-6"  | 8'-11" | 8'-5"  | 7'-11" | 7'-7"  | 7'-3"  | 6'-11" | 6'-8"  | 6'-6"  | 6'-3"  | 6'-1"  | 5'-11" |
|                      | Double         | 10'-11"                | 9'-3"  | 8'-2"  | 7'-3"  | 6'-7"  | 6'-1"  | 5'-7"  | 5'-3"  | 4'-11" | 4'-7"  | 4'-4"  | 4'-2"  | 4'-0"  | 3'-9"  | 3'-8"  |
|                      | Multiple       | 11'-10"                | 10'-1" | 8'-9"  | 7'-10" | 7'-1"  | 6'-6"  | 6'-0"  | 5'-7"  | 5'-3"  | 4'-11" | 4'-8"  | 4'-5"  | 4'-3"  | 4'-0"  | 3'-11" |

|                                                         |                                                                              |
|---------------------------------------------------------|------------------------------------------------------------------------------|
| Deflection Limit:                                       | L/180                                                                        |
| Fastening Method:                                       | (4) 1/4"-14" Through-Screws with 1 1/8" washer at every support              |
| Wind Pressure:                                          | Nominal, ASD, Service Loads                                                  |
| Thermal Differential:                                   | EXCLUDED                                                                     |
| Minimum Support Steel Properties:                       | 14 ga Grade 50 (Fu = 65 ksi)                                                 |
| DB Fastener pull-out values per supporting steel gauge: | 16 ga = 785 lbs, 14 ga = 1,035 lbs, 12 ga = 1,665 lbs, and 3/16" = 3,115 lbs |

Notes to tables: Spans shown are for negative uniform loads only. Spans may be governed by other factors including temperature differentials, deflection requirements, structural support gage, or unequal spacing of secondary. Consult Kingspan for specific project applications.



KingRib® 3 Wall Allowable Load / Span Tables

Facer Gauges: 26 ga exterior /26 ga interior

| Steel Support: 16 ga |                |                        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
|----------------------|----------------|------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Panel Thickness      | Span Condition | Negative Wind Pressure |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
|                      |                | 20 PSF                 | 25 PSF | 30 PSF | 35 PSF | 40 PSF | 45 PSF | 50 PSF | 55 PSF | 60 PSF | 65 PSF | 70 PSF | 75 PSF | 80 PSF | 85 PSF | 90 PSF |
| 2.5"                 | Single         | 10'-3"                 | 9'-2"  | 8'-5"  | 7'-9"  | 7'-3"  | 6'-10" | 6'-6"  | 6'-3"  | 6'-0"  | 5'-9"  | 5'-6"  | 5'-4"  | 5'-1"  | 4'-10" | 4'-8"  |
|                      | Double         | 10'-5"                 | 9'-0"  | 7'-11" | 7'-2"  | 6'-6"  | 6'-0"  | 5'-7"  | 5'-3"  | 4'-11" | 4'-8"  | 4'-6"  | 4'-3"  | 4'-1"  | 3'-11" | 3'-9"  |
|                      | Multiple       | 11'-6"                 | 9'-10" | 8'-8"  | 7'-10" | 7'-1"  | 6'-7"  | 6'-1"  | 5'-8"  | 5'-4"  | 5'-1"  | 4'-10" | 4'-7"  | 4'-5"  | 4'-3"  | 4'-1"  |
| 4"                   | Single         | 10'-3"                 | 9'-2"  | 8'-5"  | 7'-9"  | 7'-3"  | 6'-10" | 6'-6"  | 6'-3"  | 6'-0"  | 5'-9"  | 5'-6"  | 5'-4"  | 5'-1"  | 4'-10" | 4'-8"  |
|                      | Double         | 10'-5"                 | 9'-0"  | 7'-11" | 7'-2"  | 6'-6"  | 6'-0"  | 5'-7"  | 5'-3"  | 4'-11" | 4'-8"  | 4'-6"  | 4'-3"  | 4'-1"  | 3'-11" | 3'-9"  |
|                      | Multiple       | 11'-6"                 | 9'-10" | 8'-8"  | 7'-10" | 7'-1"  | 6'-7"  | 6'-1"  | 5'-8"  | 5'-4"  | 5'-1"  | 4'-10" | 4'-7"  | 4'-5"  | 4'-3"  | 4'-1"  |

|                                                         |                                                                              |
|---------------------------------------------------------|------------------------------------------------------------------------------|
| Deflection Limit:                                       | L/180                                                                        |
| Fastening Method:                                       | (4) 1/4"-14" Through-Screws with 1 1/8" washer at every support              |
| Wind Pressure:                                          | Nominal, ASD, Service Loads                                                  |
| Thermal Differential:                                   | EXCLUDED                                                                     |
| Minimum Support Steel Properties:                       | 16 ga Grade 50 (Fu = 65 ksi)                                                 |
| DB Fastener pull-out values per supporting steel gauge: | 16 ga = 785 lbs, 14 ga = 1,035 lbs, 12 ga = 1,665 lbs, and 3/16" = 3,115 lbs |

Notes to tables: Spans shown are for negative uniform loads only. Spans may be governed by other factors including temperature differentials, deflection requirements, structural support gage, or unequal spacing of secondary. Consult Kingspan for specific project applications.



# Contact Details

## USA

DeLand, FL: 877-638-3266  
Modesto, CA: 800-377-5110  
  
info.NA@kingspanpanels.com  
**www.kingspanpanels.us**



[Latest version here](#)

## Canada

Caledon, ON: 866-442-3594  
Langley, BC: 877-937-6562  
  
info.NA@kingspanpanels.com  
**www.kingspanpanels.ca**



[Latest version here](#)

For the most up to date version of this document,  
please scan the QR codes above or click the link.

Care has been taken to ensure that the contents of this publication are accurate, but Kingspan Limited and its subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use or application of products or methods of working are for information only and Kingspan Limited and its subsidiaries accept no liability in respect thereof.  
© Kingspan, KingRib and the Lion Device are Registered Trademarks of the Kingspan Group plc in the US, Canada and other countries. All rights reserved. © Kingspan Insulated Panels Inc.

